

Plastic Plumbers Strap Installation

Tools & Materials Needed:

- Plastic plumber's strapping
- Screws or nails (appropriate for the mounting surface)
- Drill or screwdriver
- Tape measure
- Scissors or utility knife
- Pencil or marker
- Safety gloves



Step-by-Step Installation:

1. **Measure and Cut the Strapping**

- Measure the length of strapping needed based on the pipe or fixture you are securing.
- Cut the strapping to the required length using scissors or a utility knife.
- Smooth any rough edges to prevent snags or damage to the pipe.

2. **Position the Strapping**

- Wrap the cut piece around the pipe, duct, or fixture.
- Align the perforations with the mounting surface for easy fastening.
- Allow a small gap for minor adjustments if necessary.

3. **Secure the Strapping**

- Insert a screw or nail through one of the perforations.
- Use a drill or screwdriver to fasten the strapping securely to the surface.
- Repeat on the opposite side or at multiple points for added stability.
- Ensure that the pipe or fixture is held firmly in place without excessive pressure.

4. Final Adjustments

- Confirm that the strapping is snug but not overly tight.
- Trim any excess strapping if necessary.
- Inspect the installation for stability and make any needed adjustments.

Safety Tips:

- ear safety gloves to prevent cuts while handling and installing.
- Use appropriate screws or nails depending on the mounting surface.
- Avoid overtightening to prevent damage to the pipe or strapping.
- Check the installation periodically to ensure continued security.



© 2025 Dundee Manufacturing Company. All rights reserved.

This document is the property of Dundee Manufacturing Company and may not be reproduced, distributed, or modified without written permission. Specifications are subject to change without notice.

For inquiries, contact:

Dundee Manufacturing Company

www.dundeemfg.com